

PXR-52 MS/MSK

Weatherproof Proximity Reader



FEATURES

- Compact and advanced design.
- Quick response, low interference, low power consumption and highly stable.
- Reading range up to 5cm without interference.
- Keypad provide manual input card number function(PXR-52 MSK).
- External models interface reader to co-operate and proceed storage data information(can read the remaining data) to confirm user identity and more.
- Provide sound signal and can adjust the sound by different situation.
- The case sensor provide the controller to guard against remove,when destroy by violence,the warning message will be show.
- Weatherproof, suitable to use in all places.
- Can setup to read Mifare card's serial number or card's information.

SPECIFICATIONS

HARDWARE	PXR-52MS	PXR-52MSK
Input device	1 (Case sensor)	
Keypad	----	12 Keys
Frequency	13.56MHz	
Interface type	ISO / IEC 14443A	
Reading range	5cm (max)	
Indicators	1 dual color LED (Power / Status)	
Beep tone	Buzzer	
Commucication interface	RS-485	
ELECTRICAL		
Operating voltage	DC 12V @ 200mA	
Power consumption	1.5W (max)	
Baud rate	19200bps-N-8-1	
ENVIRONMENTAL		
Operatingt temperature	0°C~55°C / 32°F~131°F	
Relative humidity	20%~95% (Non condensing)	
PHYSICAL		
Dimensions	76mm(W) x 120mm(L) x 23mm(H)	
Weight	130g	

HUNDURE

www.hundure.com

The manufacture reserves the right to revise this publication without obligation to notify any person or organization of such revisions.

PXR-52 MSMSK-CE-20030929