

# PXR-5X Series

## Weatherproof Proximity Reader



**HUNDURE**

# PXR-5X Series Weatherproof Proximity Reader

## FEATURES

- Compact and advanced design.
- Quick response, low interference, low power consumption and highly stable.
- Provide different kind of the reading range, up to 20cm ( max ).
- Interface: ABA T2, Wiegand 26 bit, RS-485.
- Weather proof, Suitable to use in all places.
- Provide LED & Buzzer control input and can fit all controllers.
- The Case sensor provide the controller to guard against remove, when destroy by violence, the warning message will be show.

## SPECIFICATIONS

HARDWARE	50ET	50EW	52ET	52ETK	52EW	52EWK	52ES	52ESK	54ET	54ETK	54EW	54EWK	54ES	54ESK	
Communication interface	T2	W	T2	T2	W	W	485	485	T2	T2	W	W	485	485	
	T2=ABA Track 2						W=Wiegand			485=RS-485					
485 Baud rate	----		19200bps-N-8-1												
Keypad	----	----	----	V	----	V	----	V	----	V	----	V	----	V	
Input device	----		1 Case sensor												
Frequency	125 KHz														
Indicators	1 dual color LED ( Power / Status )														
Beep tone	Buzzer														
Reading range	6~8cm(max)		15cm(max)						20cm(max)						
<b>ELECTRICAL</b>															
Operating voltage	DC 12V @ 200mA														
Power consumption	1.5W ( max )														
<b>ENVIRONMENTAL</b>															
Operating temperature	-10°C~55°C / 14°F~131°F														
Relative humidity	20%~95%( Non condensing )														
<b>PHYSICAL</b>															
Dimensions	PXR-50 Series					PXR-52 Series					PXR-54 Series				
	44mm(W) x 95mm(L) x 16mm(H)					76mm(W) x 120mm(L) x 23mm(H)					127mm(W) x 127mm(L) x 24mm(H)				
Weight	55g					130g					200g				

- The reading range is under the test condition without interference.

## DISTRIBUTOR

